

ES CENE

HD

2 Lines Hotel WIFI IP Phone

WS118-P



5.8G WiFi

WS118-P is a small-screen-based wireless hotel IP phone, it has fashion and technological appearance, excellent voice quality, and powerful features, and it is a new generation of intelligent phones to replace of the hotel traditional desktop terminals, It accomplished the powerful telephony features by cooperating with the communications platform, such as the call transfer, hotline, three-party conference calling, speed dial, voice mail, Do Not Disturb, etc.

WS118-P IP phones support defined 10 programmable keys ,and it can define according to the hotel different needs. such as hotel all kind of equipment sevice hotline (housekeeping, ticketing, switchboard, food and beverage, etc.), the hotel special features (alarm clock, voice mail, etc.)

Key Features

- Wireless working frequency 5.8GHz.
- Support 10 programmable keys.
- Multi-language, e.g. Chinese, English, Russian, France etc .
- 2 SIP accounts and support three-way conference, SMS.
- Excellent bracket and wall-mountable.
- 1xLAN, PoE, RJ9Headset.
- Support 15 paperless programmable keys.
- XML/LDA, BLF/BLA, Search someone in the Phone book.
- Auto-provision, HTTP/TFTP/FTP.

WS118-P Technical Datasheet

Phone Features

2 SIP accounts, Hotline
Call hold, Call waiting, Call forward, Call return
Call transfer (blind/busy/ask)
Caller ID display, Redial, Mute, DND
Auto-answer, 3-way conferencing
Speed dial, SMS, Voicemail
Message Waiting Indication LED
Tone scheme, Volume control
Direct IP call without SIP proxy
Ring tone selection/import/delete
Black list, Hand-free indicator.
Call history: dialed/received/missed (50 -entries);
Multi-Language
Soft keys programmable, Supports PC control

Advanced Features

XML Phone Book search and input & output
Enterprise phone book(800 entries)
LDAP phone book
Functions customizable keys
Support up to 15 paperless programmable keys

IP PBX System Integration

Busy lamp field (BLF), BLF list
Bridged line appearance (BLA)
DND & Forward synchronization
Intercom, Paging, Music on hold
Call pickup, Dial Plan, Call recording Anonymous
call, Anonymous call rejection
Network conference, Distinctive ringtone

Codes and Voice Features

Wideband Codec: G.722
Narrowband codec: G.711μ/A, G.723.1
G.726, G.729AB,iLBC
VAD, CNG, AEC, AGC, Full-duplex,

Security

VLAN QoS (802.1pq)
Phone lock for personal privacy protection
Admin/User 2-level configuration mode , LLDP, CDP
L2TP VPN tunneling protocol - added

Network Features

SIP v1 (RFC2543), v2 (RFC3261)
SIP connection: Proxy mode & Peering Points mode;
DNS SRV (RFC3263);
Redundant server support
NAT Traversal: STUN mode
DTMF: In-Band, RFC2833, SIP Info, Auto
HTTP/HTTPS Web Management
IP Assignment: Static/DHCP/PPPoE
Bridge/Router mode for PC port
TFTP/DHCP/PPPoE client
DNS client, NAT/DHCP server
Layer 3 ToS, DSCP

Physical Features

132x64 graphic LCD
31 keys, including 12 digital keys
2x line keys, 1x conference key, 10x programmable
keys, 1x redial key, 1x hold key, 1x speaker key, 1x
transfer key,
1x message LED
1x RJ-9 handset port
2xRJ45 10/100M Ethernet ports
Power over Ethernet ,IEEE 802.3af,class 0
Operating humidity: 10~95%
Storage temperature: up to 60°C
Power adapter: AC 100~240V input and
DC 5V/1A output

Package Features

Qty/CTN: 10 PCS
N.W/CTN: 0.799 KG
Carton Meas: 254mm*205mm*87mm

Certifications



Compatible with the platform



ES CENE COMMUNICATION CO.,LTD

Add: Floor 4 building C YueAn Industrial Park No.51 Huangcun Road Tianhe District,Guangzhou,China.

Tel: (86)20-82320720 Fax: (86)20-82326757